INSTALLATION INSTRUCTIONS Dash Pod





- 1. Determine how gauge wiring will be run:
 - A. Some pod models have a tunnel (mouse hole) for wiring.
 - B. Others will require you to create an opening in the trim or dash for wiring to pass through.
- 2. Most gauges include mounting studs that will have to be cut off or bent inwards for clearance in the pod. The standard gauge brackets normally used for mounting will not be used as the gauge is a press fit into the pod.
- 3. Install/Wire gauge per gauge installation instructions
- 4. Attach Pod to Dash using one of the following methods:
 - A. No-drill tape method: The pod can simply be pressed on and attached using the included double sided tape
 - B. Ratchet Fasteners: This method is more permanent and secure, but will require removal of the factory trim piece. Once removed, hold the pod onto the trim as it would be mounted in the vehicle. Drill four 3/16" diameter holes (two in front, two in back) through the pod and trim. Press in Ratchet Fasteners.

SERVICE

For service send your product in a well packed shipping carton to the address below. Please include a note explaining what the problem is along with your phone number. If you are sending product back for Warranty adjustment, you must include a copy (or original) of your sales receipt from the place of purchase.

Auto Meter Gauge Works Limited Lifetime Warranty

Gauge Works warrants to the consumer that all Auto Meter Gauge Works products will be free from defects in material and workmanship. Products that fail will be repaired or replaced at Auto Meter Gauge Works' option to the consumer, when determined by Auto Meter Gauge Works that the product failed due to defects in material or workmanship. This warranty is limited to the repair or replacement of parts in the Auto Meter Gauge Works Product and the necessary labor done by Auto Meter Gauge Works to effect the repair or replacement of the Auto Meter Gauge Works product. In no event shall this warranty exceed the original purchase price of the Auto Meter Gauge Works product nor shall Auto Meter Gauge Works be responsible for special, incidental or consequential damages or costs incurred due to the failure of this product. Warranty claims to Auto Meter Gauge Works must be transportation prepaid and accompanied with proof of purchase. This warranty applies only to the original purchase of product and is non-transferable. Improper use or installation, accident, water damage, abuse, unauthorized repairs or alterations voids this warranty is made solely by Gauge Works with Auto Meter being the agent to contact for warranty claims. If the partnership between Auto Meter and Gauge Works dissolves, then all warranty adjustments will be covered by the Gauge Works Co.

FOR SERVICE CONTACT: AUTO METER PRODUCTS Inc. 413 W. Elm St., Sycamore, IL 60178 USA (866) 248-6357 or Email us at service@autometer.com

© 2012 Auto Meter Products, Inc.

INSTALLATION INSTRUCTIONS Dash Pod

2650-1704-00

1. Determine how gauge wiring will be run:

- A. Some pod models have a tunnel (mouse hole) for wiring.
- B. Others will require you to create an opening in the trim or dash for wiring to pass through.
- Most gauges include mounting studs that will have to be cut off or bent inwards for clearance in the pod. The standard gauge brackets normally used for mounting will not be used as the gauge is a press fit into the pod.
- 3. Install/Wire gauge per gauge installation instructions
- 4. Attach Pod to Dash using one of the following methods:
 - A. No-drill tape method: The pod can simply be pressed on and attached using the included double sided tape
 - B. Ratchet Fasteners: This method is more permanent and secure, but will require removal of the factory trim piece. Once removed, hold the pod onto the trim as it would be mounted in the vehicle. Drill four 3/16" diameter holes (two in front, two in back) through the pod and trim. Press in Ratchet Fasteners.

SERVICE

For service send your product in a well packed shipping carton to the address below. Please include a note explaining what the problem is along with your phone number. If you are sending product back for Warranty adjustment, you must include a copy (or original) of your sales receipt from the place of purchase.

Auto Meter Gauge Works Limited Lifetime Warranty

Gauge Works warrants to the consumer that all Auto Meter Gauge Works products will be free from defects in material and workmanship. Products that fail will be repaired or replaced at Auto Meter Gauge Works' option to the consumer, when determined by Auto Meter Gauge Works that the product failed due to defects in material or workmanship. This warranty is limited to the repair or replacement of parts in the Auto Meter Gauge Works Product and the necessary labor done by Auto Meter Gauge Works to effect the repair or replacement of the Auto Meter Gauge Works product. In no event shall this warranty exceed the original purchase price of the Auto Meter Gauge Works product nor shall Auto Meter Gauge Works be responsible for special, incidental or consequential damages or costs incurred due to the failure of this product. Warranty claims to Auto Meter Gauge Works must be transportation prepaid and accompanied with proof of purchase. This warranty applies only to the original purchase or product and is non-transferable. Improper use or installation, accident, water damage, abuse, unauthorized repairs or alterations voids this warranty is made solely by Gauge Works with Auto Meter being the agent to contact for warranty claims. If the partnership between Auto Meter and Gauge Works dissolves, then all warranty adjustments will be covered by the Gauge Works Co.



12/12/12

2650-1704-00