


17P17744  
11/MAY/22  
JGB

## Bushing Installation Instructions

© 2022 Energy Suspension. All rights reserved.  
May not be reproduced, in any form, or by any means,  
without the written consent of Energy Suspension.

**ENERGY**  
**SUSPENSION**®

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673



**Note:** Remove old bushings, clean ID of the control arm eyes. Apply a light coat of "Formula 5" grease to I.D, O.D. and Flange of the bushing. Apply a light coat of grease to the OD of the sleeve. Reassemble the bolt and torque to factory specs.


17P17744  
11/MAY/22  
JGB

## Bushing Installation Instructions

© 2022 Energy Suspension. All rights reserved.  
May not be reproduced, in any form, or by any means,  
without the written consent of Energy Suspension.

**ENERGY**  
**SUSPENSION**®

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673



**Note:** Remove old bushings, clean ID of the control arm eyes. Apply a light coat of "Formula 5" grease to I.D, O.D. and Flange of the bushing. Apply a light coat of grease to the OD of the sleeve. Reassemble the bolt and torque to factory specs.


17P17744  
11/MAY/22  
JGB

## Bushing Installation Instructions

© 2022 Energy Suspension. All rights reserved.  
May not be reproduced, in any form, or by any means,  
without the written consent of Energy Suspension.

**ENERGY**  
**SUSPENSION**®

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673



**Note:** Remove old bushings, clean ID of the control arm eyes. Apply a light coat of "Formula 5" grease to I.D, O.D. and Flange of the bushing. Apply a light coat of grease to the OD of the sleeve. Reassemble the bolt and torque to factory specs.


17P17744  
11/MAY/22  
JGB

## Bushing Installation Instructions

© 2022 Energy Suspension. All rights reserved.  
May not be reproduced, in any form, or by any means,  
without the written consent of Energy Suspension.

**ENERGY**  
**SUSPENSION**®

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673



**Note:** Remove old bushings, clean ID of the control arm eyes. Apply a light coat of "Formula 5" grease to I.D, O.D. and Flange of the bushing. Apply a light coat of grease to the OD of the sleeve. Reassemble the bolt and torque to factory specs.