



# Owner's Manual with Installation Instructions

## Banks A-Pillar Mount Gauge Mounting

**2015+ Ford F-150**  
**2017+ Ford Super Duty**

THIS MANUAL IS FOR USE WITH SYSTEM 63338

Gale Banks Engineering  
546 Duggan Avenue • Azusa, CA 91702  
(626) 969-9600 • Fax (626) 334-1743

Product Information & Sales: (888) 635-4565  
Customer Support: (888) 839-5600  
Installation Support: (888) 839-2700

**bankspower.com**

# General Installation Practices

Dear Customer,

If you have any questions concerning the installation of your Banks A-Pillar Mount System, please call our Technical Service Hotline at (888) 839-2700 between 7:00 am and 4:00 pm (PT). Watching our how-to video (link on the cover) may alleviate any further questions. If you have any questions relating to shipping or billing, please contact our Customer Service Department at (888) 839-5600.

Thank you.

**1.** Before starting work, familiarize yourself with the installation procedure by reading all of the instructions.

**2.** Disconnect the negative (ground) cable from the battery (or batteries, if there are two) before beginning work.

**3.** Route and tie wires and hoses a minimum of 6" away from exhaust heat, moving parts and sharp edges. Clearance of 8" or more is recommended where possible.

**4.** During installation, keep the work area clean. Do not allow anything to be dropped into intake, exhaust, or lubrication system components while performing the installation, as foreign objects will cause immediate engine damage upon start-up.

## Tools Required:

- Phillips screwdriver
- 1/4" or 3/8" drive ratchet with 10 mm socket

## What's Included

Item #	Description	Part #	QTY
1	Pillar Mount Kit, Single Gauge	63338-01	1
2	Owner's Manual	96423	1

Figure 2



# A-Pillar Mount Installation

**1.** Open the two bolt covers on the factory grab handle and remove the two bolts with a 10mm socket. See **Step 1**.

## **Step 1**



**2.** Remove stock pillar by pulling towards you and sliding up, releasing the two tabs from the dash. Disconnect speaker wire harness to fully remove stock pillar. See **Step 2**.

## **Step 2**



**3.** Run the applicable iDash wiring up through the stock pillar location in preparation for the Banks Pillar. Remove speaker from stock pillar and reinstall onto Banks pillar using the supplied 4-40 screws. See **Step 3**.

## **Step 3**



**4.** Install supplied snap nut onto the bottom end of the top slot. Reconnect speaker harness and reinsert tabs on the lower portion of the Banks pillar into the dash near the windshield. See **Step 4**.

## **Step 4**



**5.** Connect iDash before fully installing the Banks pillar. Insert supplied black screw into Banks pillar and align with previously installed snap nut. Finish install by tightening screw into snap nut. Take care to not overtighten screw. **Step 5**.

## **Step 5**



Gale Banks Engineering  
546 Duggan Avenue • Azusa, CA 91702  
(626) 969-9600 • Fax (626) 334-1743

Product Information & Sales: (888) 635-4565  
Customer Support: (888) 839-5600  
Installation Support: (888) 839-2700

**bankspower.com**