

Part Number:

Product SUPPLEMENTARY BUMPER CUT INSTRUCTIONS TO SUIT DELUXE, SUMMIT, SUMMIT SAHARA AND ALLOY BARS (NO ADAPATIVE CRUISE

CONTROL OR PARK ASSIST)

Suited to FORD RANGER MY19, 08/2018 ON, NON ADAPATIVE CRUISE OR PARK

vehicle/s: ASSIST ONLY

NOTE: READ THESE INSTRUCTIONS IN CONJUNCTION WITH F/INST INCLUDED

WITH 3440400, 3440510, 3440530, 3940420 & 744020

FITTING PROCEDURE UPDATE FOR RANGER MY19 MODELS ONLY (NON ADAPTIVE CRUISE OR PARK ASSIST)

1. USE IN CONJUNCTION WITH FITTING INSTRUCTIONS INCLUDED WITH THE RELEVANT BAR.

2. WIRING UPDATE:

Following fitting instructions 3789197 supplied in kit 6821287; install the LED combination lamp looms (also supplied in the same kit).

Notes:

- -Use a test light or multimeter to pick the appropriate wire to attach the loom to.
- -Cover each joint with either insulation tape or heat shrink tube.

LED **Vehicle Wire Function RANGER XL** Wire Black/Purple (RHS) Ground Black Black/Green (LHS) Green Blue/Orange (RHS) Indicator Blue/Orange (LHS) Red Brown/Yellow (RHS) Clearance Green/Orange (LHS)





INDICATOR

*LHS shown

BEFORE TRIM




AFTER TRIM 29mm MOUNT SLOT CTR (TYP) 834mm CENTRES

3. **BUMPER TRIM**;


- 4. Continue the line from the lower edge of the trim template on the RHS across the top of the bumper following the top-front ridge of the bumper and connect this to the lower edge of the trim template marking on the LHS
- 5. Also remove two semi-circular notches on the front edge of the trimmed bumper to clear the Bull Bar uprights as shown.








Warning: Cutting operations can result in flying metal debris, safety glasses should be worn.



IF FITTING A WINCH:

6. For Warn Magnum, Warn Platinum, Smittybuilt and Bushranger control boxes, an additional centralised Bumper cut is required as shown at left

CLOSE UP VIEW: BUMPER CUT LOCATION







Warning: Cutting operations can result in flying metal debris, safety glasses should be worn.

- 7. Apply a continuous strip of pinch weld to the bumper trim recess edges, extending onto the front bumper trim edges on each side as shown at left.
- 8. Some winches may require an extended bumper trim to clear the winch control box handle as shown at left (eg for Warn Zeon)





Warning: Cutting operations can result in flying metal debris, safety glasses should be worn.

