

Part Number: 3440510

# Product SUMMIT BULL BAR (NO FRONT SENSORS OR RADAR)

Description:

# Suited to FORD RANGER MY19, 08/2018 ON, XL MODELS ONLY

vehicle/s:

### NOTE: READ THESE INSTRUCTIONS IN CONJUNCTION WITH F/INST 3789423 DATED 10/04/2017

# FITTING PROCEDURE UPDATE FOR RANGER MY19 XL MODELS ONLY

- 1. IGNORE ALL STEPS RELATING TO EVEREST MODELS.
- 2. IGNORE STEPS: 16-18, 42-43, 54-61, 62-78, 91-98, 118, 120-121. THEY ARE NOT APPLICABLE FOR THE RANGER MY19 XL MODEL VEHICLE.

### 3. WIRING UPDATE: (REPLACES STEP 24):

Following fitting instructions 3789197 supplied in kit 6821287; install the LED combination lamp looms (also supplied in the same kit).

#### Notes:

-Use a test light or multimeter to pick the appropriate wire to attach the loom to. -Cover each joint with either insulation tape or heat shrink tube.

CL	EARANC	CE

Function	LED Wire	Vehicle Wire RANGER XL
Ground	Black	Black/Purple (RHS) Black/Green (LHS)
Indicator	Green	Blue/Orange (RHS) Blue/Orange (LHS)
Clearance	Red	Brown/Yellow (RHS) Green/Orange (LHS)



\*LHS shown



- 4. **BUMPER TRIM;** (REPLACES STEPS 42-43): Continue the line from the lower edge of the trim template on the RHS across the top of the bumper following the top-front ridge of the bumper and connect this to the lower edge of the trim template marking on the LHS
- 5. Also remove two semi-circular notches on the front edge of the trimmed bumper to clear the Bull Bar uprights as shown.



### Last Rev Date: 31/08/2018

#### Page 1 of 2 Fitting instructions# 3789866

Copyright © 2005 by ARB Corporation Limited. All rights reserved, this document must not be reproduced without the express authority of ARB Corporation Ltd

